



## DESCRIPTION

High quality vinyl powder coating. Fine powder coating.  
Complies with French Standard NF T30-608.

## FIELD OF USE

It is an interior finishing plaster intended for the careful raking and coating of cement and plaster plaster substrates. It offers very white, hard, smooth and not very absorbent surfaces which constitute the base of choice for the implementation of all paints.  
It is easily applied with a spatula or float or coating knife.

## TECHNICAL CHARACTERISTICS

- Aspect : Matt.
- Color : White.
- Spreading-rate : 2 to 3 m<sup>2</sup>/kg.
- Dry extract by weight : 100%.
- Pot life of the mixture: 6 hours.

## SURFACE PREPARATION

The work must be done in accordance with standard NF DTU59.1 and will be carried out with the greatest care.

## CONDITIONS AND METHODS OF APPLICATION

Recommended equipment: spatula, float or coating knife.  
Application limit: Do not apply on condensing or frozen substrates, at temperatures below 5 ° C, or at relative humidity above 70%.

## APPLICATION DETAILS OF USAGE

Thinner: Water

Prepare a bucket of water (9 to 10 liters) and add the product (1 bag of 25 kg) gradually, while stirring. Mix until a homogeneous and smooth paste is obtained. Let this dough rest 10 minutes before using. Before application, it is necessary to ensure that the funds are well dusted, the visible metal parts must be isolated.

## DRYING TIME

Dry: 5 hours.  
Interval between coats: 5 hours.

## STORAGE

The product can be stored for up to 2 years in good storage conditions away from sunlight, it is nevertheless recommended to shake the product before use.

## PACKAGING

5 kg, 25 kg

## HEALTH & SAFETY

Health and safety information and precautions for use are detailed on the safety data sheet N° 11.

Edition : July 2020 by Colorado 07/20 (DC28 D).

N.B: The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted.  
This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001