# TECHNICAL DATA SHEET:

# **ACRYSAT**





# **DESCRIPTION**

Slightly satin emulsion paint based on acrylic resin. Contains titanium dioxide, calcium carbonate, and water.

#### **FIELD OF USE**

For the interior: A very smooth and very washable paint with a slight satin finish.

For the exterior: A weather-resistant facade paint. Its appearance is smooth and slightly satin.

#### **TECHNICAL CHARACTERISTICS**

Aspect : Slightly satin.

 Colors: A choice. Special colors are delivered for orders over 100 kg.

Spreading-rate: 13 to 15 m<sup>2</sup>/Litre depending on the porosity of the support.

Density: 1,35 +/- 0,05 at 25°C.Viscosity: 100 +/- 5 KU at 25°C.

### **SURFACE PREPARATION**

The work must be done in accordance with standard NF DTU59.1 and will be carried out with the greatest care.

# **CONDITIONS AND METHODS OF APPLICATION**

It is applied with a roller or possibly a brush on clean, dry and dust-free bases, preferably covered with a matt vinyl paint. Generally, two coats are applied diluted according to the porosity of the support.

Application limit: Do not apply on condensing, frozen substrates, at temperatures below 5 ° C and / or relative humidity above 70%.





#### **APPLICATION DETAILS OF USAGE**

Dilution: Water
\* 1st coat: 20 to 30%.
\* 2nd layer: 10% to 20%.

#### **DRYING TIME**

Drying at 20  $^{\circ}$  C and 60% humidity:

- \* Dust dry: 30 min.
- \* Dry: 45 min.
- \* Interval between coats: minimum 4 hours.

## **RECOMMENDED SYSTEM**

#### ■ INTERIOR

SYSTEM	NUMBER OF COATS
COLOPRIM or COLOFIX	1
SUPER PATENDUIT SP88	2
COLOSTOP	1
ACRYSAT	2

# **STORAGE**

The product can be stored for up to 2 years under good storage conditions away from sunlight and frost in its original closed packaging. It is nevertheless recommended to shake the product before use.

# **PACKAGING**

3L, 10 L.

## **HEALTH & SAFETY**

Health and safety information and precautions for use are detailed on the safety data sheet  $N^\circ$  53.

Edition: October 2021 by Colorado 10/21 (DC28 D).

N.B: The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted.

This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001