



DESCRIPTION

Decorative coating based on vinyl emulsion. Highly decorative painting that has an old-fashioned marbled appearance. Suitable for all spaces such as apartments, halls and large rooms.

FIELD OF USE

Recommended for application on interior walls.

TECHNICAL CHARACTERISTICS

- Aspect : Pasty product.
- Colors: White and can be tinted with Shades 2000.
- Spreading-rate : 2 m²/kg (in 2 layers).
- Density : 1.58 +/- 0.05 at 25°C.
- Viscosity : 1000 poises +/- 200 at 25° C.

SURFACE PREPARATION

The work must be done in accordance with standard NF DTU59.1 and will be carried out with the greatest care.

CONDITIONS AND METHODS OF APPLICATION

The support (cement plaster) must be sound, dry and dust free.
 On a previously prepared substrate, apply a medium and even coat using a lacquer roller. Before the product dries, using a triangular spatula or a stainless steel float, lightly crush in all directions.
 Work by surface of 1 to 2 m² (without risk of rework).
 OPTION: The application of a top coat of COLOCIRE water-based shoe polish protects and maintains the AMBRA BRILLANT paint while increasing its shine and washability.
 NOTE: The use of COLOCIRE water-based shoe polish makes the color of AMBRA BRILLANT a little darker.

APPLICATION DETAILS OF USAGE

Dilution: Product ready to use. Do not dilute.

DRYING TIME

12 hours approximately.
 Recoverable : 6 hours.

RECOMMENDED SYSTEM

■ INTERIOR

SYSTEM	NUMBER OF COATS
COLOPRIM or COLOFIX	1
COLENDUIT EXTRA B805 or SP88	2
COLOFIX	1
AMBRA	2
CIRAGE AMBRA or COLOCIRE (option)	1

STORAGE

The product can be stored for up to 2 years in good storage conditions away from sunlight, it is nevertheless recommended to shake the product before use.

PACKAGING

1 Kg, 5 kg, 25 kg.

HEALTH & SAFETY

Health and safety information and precautions for use are detailed on the safety data sheet N° 18.

Edition : March 2022 by Colorado 03/22 (DC28 D).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted. This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001