





DESCRIPTION

Depolluting paint. This paint purifies the interior air thanks to an active principle which destroys the aldehydes present in the interior air. The destruction is 60% of formaldehyde in 24 hours. Test report n°20-CO-11351.

FIELD OF USE

All interior surfaces properly prepared.

TECHNICAL CHARACTERISTICS

Aspect : Velvety matte.

Color : White.

Spreading rate: 7 to 9 m²/kg.

■ Density: 1,45 +/- 0,05 at 25°C. Complies with the NM

ISO 2811-1 (2008) standard. ■ Viscosity: 135 +/- 5 KU at 25°C.

SURFACE PREPARATION

The work must be done in accordance with the NF DTU59.1 standard and will be carried out with the greatest care.

CONDITIONS AND METHODS OF APPLICATION

Limits of application: Do not apply on condensing or frozen support, by temperature lower than 5°C, and higher than 35°C, nor by relative humidity higher than 65%.

APPLICATION DETAILS OF USAGE

Dilution: Ready to use.

Close the unfinished cans to reuse the paint.

Reusing paint is a good way to reduce the environmental

impact of products over their entire life cycle. Application equipment: Roller or brush or spray gun Cleaning of equipment: With water, immediately after use.

RECOMMENDED SYSTEM

■ INTERIOR

SYSTEM	NUMBER OF COATS
COLOFIX	1
CLEAN AIR	2

DRYING TIME

At 20° C and 60% humidity:

* Dust free: 30 min

* Dry : 2 hours

* Interval between coats: 4 hours minimum.

STORAGE

The product can be stored for up to 2 years under good storage conditions away from the sun, however it is recommended to shake the product before use.

PACKAGING

5 kg.

HEALTH & SAFETY

Health and safety information and precautions for use are detailed on Safety Data Sheet N° 313.

Edition: February 2022 by Colorado 02/22 (DC28 D).

N.B: The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted.

This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001