



DESCRIPTION

Semi-gloss emulsion paint based on vinyl resin and water.

FIELD OF USE

COLOAQUA is a water-based lacquer specially designed for new work indoors and outdoors such as bathrooms, kitchens and exhibition walls. COLOAQUA is distinguished by:

- * A very high opacifying power.
- * Very easy to apply
- * Very high exterior durability (maximum resistance and permeability to water vapor).
- * Very low odor during application

TECHNICAL CHARACTERISTICS

- Aspect : semi-gloss.
- Colors : Delivered in white, it can be tinted with Shades 2000. Special shades are delivered for orders over 100 Kgs.
- Spreading-rate : 14 to 16 m²/Kg depending on the porosity of the support.
- Density : 1,31 ± 0,05 at 25°C.
- Viscosity : 100 ± 5 KU with a Krebs viscometer at 25 ° C.

SURFACE PREPARATION

The work must be done in accordance with standard NF DTU59.1 and will be carried out with the greatest care.

CONDITIONS AND METHODS OF APPLICATION

Recommended material: Brush or roller.
 Can be applied directly to concrete. If the substrate presents a high risk of support for microorganisms (algae, fungus) ask for the version with Fungicide.
 Do not apply on substrates condensing or frozen at temperatures below 5 ° C or at relative humidity above 70%.

APPLICATION DETAILS OF USAGE

Dilution: With water

DRYING TIME

Drying at 20 ° C and 60% humidity:
 * Dust dry: 30 min.
 * Dry: 4 hours.
 * Recoatable: 2 hours.

RECOMMENDED SYSTEM

■ INTERIOR

SYSTEM	NUMBER OF COATS
COLOPRIM or COLOFIX	1
SUPER PATENDUIT SP 88	2
COLOSTOP	1
COLOAQUA	2

STORAGE

The product can be stored for up to 2 years in good storage conditions away from sunlight and frost in its original closed packaging. It is nevertheless recommended to shake the product before use.

PACKAGING

4 kg, 20 kg.

HEALTH & SAFETY

Health and safety information and precautions for use are detailed in the safety data sheet N ° 15.

Edition : July 2020 by Colorado 07/20 (DC28 D).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted. This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001