COLOCLEAN





COLOCLEAN is a 100% satin acrylic paint designed to meet the specific needs of the healthcare sector. It is an innovative, washable water-based acrylic paint that actively prevents the growth of bacteria and viruses with active agents. It is effective against various strains of bacteria and viruses and thus reduces the risk of contamination in hospital environments. Its very closed paint film destroys 99.97% human Coronavirus type viruses by contact and 99.9% bacteria. Complies with ISO 22196: 2011 standards (Bacteria), and ISO 21702: 2019 (Viruses).

FIELD OF USE

All rooms, walls and ceilings.

TECHNICAL CHARACTERISTICS

Aspect : Satin.Colors : White.Spreading-rate :

 $+/-12 \text{ m}^2/\text{L}$, variable depending on the substrate and the type of preparation.

+/- 10 m2/ Kg, variable depending on the substrate and the type of preparation.

Density: 1,20 +/- 0,05 at 25°C.

Viscosity: 120 +/- 5 KU at 25°C.

SURFACE PREPARATION

The work must be done in accordance with standard NF DTU59.1 and will be carried out with the greatest care.

CONDITIONS AND METHODS OF APPLICATION

It is applied with a roller or possibly a brush on clean, dry and dust-free bases. Generally, two coats are applied, the first diluted to 5% the second without dilution. Application limit: Do not apply on condensing, frozen substrates, at temperatures below 5 ° C and / or relative humidity above 70%.





RECOMMENDED SYSTEM

■ INTERIOR

SYSTEM	NUMBER OF COATS
COLOPRIM or COLOFIX	1
ENDUIT SP88	2
COLOSTOP (OPTIONAL)	1
COLOPRIM or COLOFIX	1
COLOCLEAN	2

APPLICATION DETAILS OF USAGE

Dilution: 5% Water.

DRIYING TIME

- * Dust dry: 30 min.
- * Dry: 2 hours.
- * Interval between coats: minimum 4 hours.

STORAGE

The product can be stored for up to 2 years under good storage conditions away from sunlight and frost in its original closed packaging. It is nevertheless recommended to shake the product before use.

PACKAGING

5 kg.

HEALTH & SAFETY

Health and safety information and precautions for use are detailed in the safety data sheet N ° 152.

Edition: November 2021 by Colorado 11/21 (DC28 D).

N.B: The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted.

This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001