



DESCRIPTION

Thick decorative coating based on acrylic copolymers in aqueous phase.

Classification: NF T-36-005: Family II, class 1b.

FIELD OF USE

Particularly suitable for crimping and the protection of facades, corridors, halls, waiting rooms, stairwells etc ... Very high water vapor permeability, excellent water resistance.

TECHNICAL CHARACTERISTICS

- Aspect : Pasty product. Granite aspect and a natural matt.
- Colors : White, it can be tinted with our Tints 2000.
- Spreading-rate : 1 to 1,5 m²/kg (depending on the nature of the support and the roll used).
- Density : 1,50 +/- 0,05 at 25°C of the PG.
1,60 +/- 0,05 à 25°C of the GG.
- Viscosity : 2000 +/- 200 poises at 25° C (Brookfield).

SURFACE PREPARATION

The work must be done in accordance with standard NF DTU59.1 and will be carried out with the greatest care.

CONDITIONS AND METHODS OF APPLICATION

The substrates will be sound, clean, cohesive and free of any residue or other which could affect the good adhesion of COLOGRAINS.

Recommended temperature between 5 °C and 35 °C.

Do not apply on a support frozen or thawing, hot or in full sun, soaked or in rain and strong wind.

Apply (without diluting) with a 20 cm knife and simultaneously bring out the desired decorative appearance using the appropriate roller (serrated roller, honeycomb roller or others).

APPLICATION DETAILS OF USAGE

Dilution: Running water.

DRIYING TIME

Drying at 20 ° C and 65% humidity:

- * Dust free: 1h30min.
- * Dry: 3 hours.
- * Recoatable: 12 hours.
- * Total hardening: 15 days.

RECOMMENDED SYSTEM

SYSTEM	NUMBER OF COATS
COLOPRIM or COLOFIX	1
COLOGRAINS	1 à 2

STORAGE

The product can be stored for up to 2 years in good storage conditions away from the sun, it is nevertheless recommended to shake the product before use.

PACKAGING

20 kg.

HEALTH & SAFETY

Health and safety information and precautions for use are detailed in the safety data sheet N° 37.

Edition : October 2021 by Colorado 10/21 (DC28 D).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted.

This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001