



DESCRIPTION

? Sff bS[fTSeW a` h[k^V[eWb[a` ž 38@ADF%(Ž "" USee, 8S_ [k; ŽUSee) Sž

FIELD OF USE

5A>A? 3J US` TWSbb^VW fa [fV[adS` V VjVfV[ad _ Sea` d[VjVfV[adi aaVi ad` S` V b^SefV[; f[eaVadV[ed ZSeShV[YaaVi Z[fVW[es` VSYaaV LahV[Y bai V[

TECHNICAL CHARACTERISTICS

- 3dbWf, ? Sfz
- 5a`ad, 6W[hV[i Z[fVUS` TWf[fW i [fZ agdF[fe \$"" ž
- EbdV[YžSFW, 3bb[] SFV[_ %Y VVWV[Y a` fZW badefk aXfZWgbbadž
- Densitk : 1,75 ± 0,05 Kg/L Sf 25° C.
- Viscositk : 250 ± 50 4da] X[VW h[ela_ VVdSf \$` »ž

SURFACE PREPARATION

FZW ad` _ gefTWa` W[SUad/S` UW [fZ fZW@86FG` +# efS` VSd/S` Vi [^TWUSd[V agfi [fZ fZVWd[Vf USdV

CONDITIONS AND METHODS OF APPLICATION

3bb`k i [fZ Sd` V[adSTdjeZ>[_ [feaXSbb`[USf[a` , 6a` af Sbb`k a` La` VV[e] Y adX[W egbbadfeTk fW_ bV[SfgdV` ai VdFZS` ` »5i` adTk d[Vf[hVZg_ [Vfk Z[YZVdFZS`)" . ž

APPLICATION DETAILS OF USAGE

Dilution :
 * #ef LbSf, #` fa #` . i SfV[
 * \$` V LbSf, ' fa #` . i SfV[

DRYING TIME

3f \$` »5 S` V (" . Zg_ [Vfk,
 * 6ck, % _ [ž
 * DV[ahV[ST` W, & Zž

RECOMMENDED SYSTEM

■ 7J F7D;AD

EKEF?	@G? 47D A85A3FE
ENDUIT FACADE P20 odP10	1od2
COLOPRIM odCOLOFIX	1
COLOMAX	2

■ ;@F7D;AD

EKEF?	@G? 47D A85A3FE
COLOPRIM odCOLOFIX	1
COLENDUIT Extra B505 odSP88	2
COLOMAX	2

STORAGE

FZWbdaVgUf US` TWefadW` Xadgb fa \$ kV[edg` VVd YaaV efadSYWLa` V[f[a` eSi Sk X[_ fZW[eg` i Zai VV[[[edV[_ WVVW fa eZS] WfZWbdaVgUf TWadVgeV[

PACKAGING

1 kg, 5 kg, 10 kg, 30 kg, 45 kg.

HEALTH & SAFETY

: V[fZ S` V eSXV[[Xad` Sf[a` S` V b[V[Sgf[a` e XadgeW Sd/VV[S[VW a` fZV[esXV[VSFS eZVWV @# \$&

7V[f[a` , March \$` \$\$ Tk 5a`adSva` " 3!\$\$/65\$* 6fz

@Z4, FZWbgbaeWaxfZ[eFVWZ` [US^VSFS eZVWV [efa bda]VWV[Xad` Sf[a` a` fZWbcbVd[V[VeXagdbdaVgUfZfZWV[Xad` Sf[a` La` fs[W fZWV[[eTSeW a` agd UgdVf]` ai VVYVaxfV[feUSd[VW agfi [fZ SLa` eS` fLa` UWd` XadaT[VV[hfk SUadV[Y fa fZWLa` V[f[a` eaXgeW` SUad/S` UW [fZ efS` VSd/ead6FG [XadW : ai VV[fZWV[Xad` Sf[a` US` ` af d[V` SUAS` Sbbcbdc[SfVWV[Ub]f[a` S` V fZWefSfWaxfZW[; Vefa TVbS[fWž FZ[eVW[ub]hVWVZ` [US^eZVWV US` UW[S` V d[V` SUW[S` k eZVWV d[Vf[Y fa fZW[es` VbdaVgUfZfZWV[STahVWVZ` [US^VSFS VaV[af [b`k SULL[fS` UMaXfZW YgSdS` fV[ž 5` a` eWfZVbaf f[YZf`k SXVd[geV[; Wb bdaV[hVfZVWV h[da` _ WfTk` af V[ebae] Y aXi SefV[fZWV[eadZageV[Za` Vi SefV[V[esW[Vgd kagdV_ bfk `Sdfa S dV[KU[Y UW fV[ž 8adkagd[geW bdaVgUf b V[esW[fSUF kagd` aUS` SgfZad[fV[Xad` Xad` Sf[a` a` V[ebaeS` S` V La` VV[f[a` ž

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001