



DESCRIPTION

High quality coating designed to protect and decorate swimming pools and ornamental ponds. Characterized by high resistance to water immersion and to various water sanitation products such as chlorine, and great waterproofing power.

FIELD OF USE

Colopiscine can be applied on concrete covering or for renovation of an already painted swimming pool.

TECHNICAL CHARACTERISTICS

- Colors: Azure blue, special colors are available on request for orders over 120 Kg.
- Aspect: Satin.
- Density : 1,35 +/- 0,05 at 25°C.
- Spreading-rate theoretical : 8.3 m²/Kg/50µm.
- Volume-solids : 41 +/- 2%.
- Recommended thickness: 50 µm.

SURFACE PREPARATION

The work must be done in accordance with standard NF DTU59.1 and will be carried out with the greatest care.

APPLICATION PROPERTIES

- * Colopiscine is applied by roller or spray.
- * During application the temperature should be between 5 to 35 C °.
- * The first diluted coat allows penetration, fixation and reinforcement of the support.
- * The second layer is used for embellishment.
- * Support recognition is essential to ensure the sustainability of the system.

APPLICATION DETAILS OF USAGE

- Dilution:
- *D77 and D33 .
 - *Brush / roller: up to 15%.
 - *Spray : adapt the dilution according to the spray and the pressure.

DRYING TIME

At 20 ° C and 65% humidity:

- *Through-dry : 30 min.
- * Manipulation : 3 h.
- * Recoatable: 24 h.

Leave to dry for 7 days before filling the pool with water.

RECOMMENDED SYSTEM

- On cement or concrete:

SYSTEM	NUMBER OF COATS
VERNIS IMPREX	1
COLOPISCINE	2

- On tiling in good condition:

SYSTEM	NUMBER OF COATS
VERNIS BETONIX	1
COLOPISCINE	2

- Other media: contact us.

STORAGE

The product can be stored for up to 2 years under good storage conditions out of direct sunlight in its original packaging. It is nevertheless recommended to shake the product before use.

PACKAGING

5 Kg.

HEALTH & SAFETY

Health and safety information and precautions for use are detailed on the safety data sheet N°167.

Edition : July 2020 by Colorado 07/20 (DC28 D).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted. This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001