



DESCRIPTION

Thick decorative coating based on copolymers in aqueous phase.

FIELD OF USE

Particularly suitable for the construction and protection of facades, corridors, halls, waiting rooms, stairwells, etc. Very high water vapor permeability, excellent water resistance.

TECHNICAL CHARACTERISTICS

- Aspect : Pasty product. Granite aspect and natural matt
- Colors : White and can be tinted with Shades 2000.
- Spreading-rate : 1 to 3 m²/kg (depending on the nature of the support and the roll used).
- Density : 1,50 +/- 0,05 at 25°C.
- Viscosity : 2000 +/- 200 poises at 25° C (Brookfield).

SURFACE PREPARATION

The work must be done in accordance with standard NF DTU59.1 and will be carried out with the greatest care.

CONDITIONS AND METHODS OF APPLICATION

Whether new or old supports, the surface must be dry, sound and free of all traces of contaminants. Apply (without diluting) with a 20 cm knife and simultaneously bring out the desired decorative appearance using the appropriate roller (serrated roller, honeycomb roller or others).

APPLICATION DETAILS OF USAGE

Dilution: Running water.

DRIYING TIME

- Drying at 20 ° C and 60% humidity:
- * Dust free: 1h30min.
 - * Dry: 3 hours.
 - * Recoatable: 12 hours.
 - * Total hardening: 15 days.

RECOMMENDED SYSTEM

SYSTEM	NUMBER OF COATS
COLOPRIM or COLOFIX	1
COLOREX PG	1

STORAGE

The product can be stored for up to 2 years in good storage conditions away from direct sunlight and frost in its original closed packaging. It is nevertheless recommended to shake the product before use.

PACKAGING

5 kg, 25kg.

HEALTH & SAFETY

Health and safety information and precautions for use are detailed in the safety data sheet N°37.

Edition : November 2020 by Colorado 11/20 (DC28 D).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted. This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001