



## DESCRIPTION

Finishing paint based on modified acrylic resins, having good mechanical resistance, good retention of gloss and color.

## FIELD OF USE

Good corrosion protection in combination with one or two coats of IRON EPOXY primer.

## TECHNICAL CHARACTERISTICS

- Aspect : Satin.
- Color: A choice.
- Spreading-rate: 10m<sup>2</sup> / L / 60µm.
- Density: 1.6 ± 0.05.
- Volume-solids : 60 ± 2%.

## SURFACE PREPARATION

The work must be done in accordance with standard NF DTU59.1 and will be carried out with the greatest care.

## APPLICATION PROPERTIES

Application equipment: airless or pneumatic spray, brush and roller.

Application limit: Do not apply on condensing or frozen support, at temperature below 5 ° C, or at relative humidity above 70%.

Support temperature : between 5 ° C and 35 ° C.

## APPLICATION DETAILS OF USAGE

Dilution: Thinner; D55, D33, D77 (5 to 15%).

## RECOMMENDED SYSTEM

- On metal; previously prepared

SYSTEM	NUMBER OF COAT
PRIMAIRE IRON EPOXY	1
INTERMIDIAIE IRON EPOXY	1 to 2
COLOTEX	1 to 2

- On concrete and cement;

SYSTEM	NUMBER OF COAT
VERNIS IMPREX or BETONIX	1
COLOTEX	2

## DRYING TIME

Drying at 20 ° C and 60% humidity:

- \* Surface-dry : 10 min
- \* Through-dry : 30 Hours
- \* Recoverable : 12 Hours

## STORAGE

The product can be stored for up to 1 year in good storage conditions out of direct sunlight, in its original packaging. It is nevertheless recommended to shake the product before use.

## PACKAGING

20 L .

## HEALTH & SAFETY

Health and safety information and precautions for use are detailed on the safety data sheet N° 175-1.

Edition : October 2020 by Colorado 10/20 (DC28 D).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted. This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001