



DESCRIPTION

COLOTITANE is a matte paint based on acrylic copolymer, specially designed for new exterior work. Nevertheless it is very popular for interior decoration. COLOTITANE is distinguished by very good whiteness, very high opacifying power, very easy to apply, high yield even on absorbent substrates and very good washability.

FIELD OF USE

Recommended for application on exterior and interior walls of concrete, plaster and plaster.

TECHNICAL CHARACTERISTICS

- Aspect : Mât.
 - Color : Supplied in white and can be tinted with Shades 2000.
 - Spreading-rate : 10 to 12 m²/kg on Colofix, compliant with ISO 23811 (2009).
 - Density : 1,54 +/- 0,05 at 25°C, Complies with NM ISO 2811-1 (2008).
 - Dry extract (by weight) : 65 +/- 2%, Compliant with ISO3233-3 (2015).
 - Viscosity : 600 +/-50 P with the Brookfield viscometer at 25° C.
 - Viscosity : 125 +/- 5 KU at 25°C, Complies with ASTM D561 (1997).
- AFNOR classification (NF T36-005): Family I class 7b2. C.O.V. classification (directive 2004/42 / CE):
 EU limit value of this product category A / d: 80g / l (2010). This product contains a maximum of 10.0 g / l VOC.
 EU ECOLABEL: FR / 044/056.

SURFACE PREPARATION

The work must be done in accordance with standard NF DTU59.1 and will be carried out with the greatest care.

CONDITIONS AND METHODS OF APPLICATION

Recommended material: Brush or roller.
 Do not apply on condensing or frozen substrates at temperatures below 5 ° C nor at humidity above 70%.

DILUTION & ADVICE

1st coat diluted with 10% water if necessary.
 Avoid wasting paint, estimate how much paint you need.
 Close any unfinished jars so that the paint can be reused.
 Reusing paint is a good way to reduce the environmental impact of products over their entire life cycle.
 Estimate the quantity needed before purchase in order to optimize cost and waste: 25kg +/- 140 m².
 For information on disposal methods, contact the local authorities.

DRYING TIME

- Drying at 20 ° C and 60% humidity:
- * Dust free: 15 min
 - * Dry: 30 min
 - * Intervalle entre couches : 4 heures minimum.

RECOMMENDED SYSTEM (contact us)

■ EXTERIOR (*):

SYSTEM	NUMBER OF COATS
ENDUIT FACADE P20 or P10	1
COLOPRIM or COLOFIX	1
COLOTITANE	2

■ INTERIOR:

SYSTEM	NUMBER OF COATS
COLOPRIM or COLOFIX	1
COLOTITANE	2

(*) System recommended to protect the support of the carbonation thanks to its resistance to CO₂ diffusion.

STORAGE

The product can be stored for up to 2 years in good storage conditions away from sunlight and frost in its original closed packaging. It is nevertheless recommended to shake the product before use.

PACKAGING

13 L.

HEALTH & SAFETY

Health and safety information and precautions for use are detailed in the safety data sheet N ° 187.

Edition : July 2020 by Colorado 07/20 (DC28 D).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted.
 This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees.
 Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001