



## DESCRIPTION

Matt paint based on acrylic copolymers for careful work.

- \* Great whiteness;
- \* Great opacifying power;
- \* Great ease of application.

## FIELD OF USE

COLOVINYL 900 can be applied to masonry, woodwork and plaster coverings.

## TECHNICAL CHARACTERISTICS

- Aspect : Matt white.
- Spreading-rate : 7 to 9 m<sup>2</sup>/Kg by layer depending on the porosity of the support, in accordance with ISO 23811 (2009).
- Density : 1,65 ± 0,05 at 25°C, complies with NM ISO 2811-1 (2008).
- Viscosity : 400 ± 50 poises at 25°C at Brookfield.

## SURFACE PREPARATION

The work must be done in accordance with standard NF DTU59.1 and will be carried out with the greatest care.

## CONDITIONS AND METHODS OF APPLICATION

COLOVINYL 900 can be applied by roller or brush. Limit of application: Do not apply on condense or frozen substrates, at temperatures below 5 ° C and above 35 ° C, or at relative humidity above 80%.

## APPLICATION DETAILS OF USAGE

- Dilution:
- \* 1st layer 15 to 20% water.
  - \* 2nd layer +/- 10% water.

## DRYING TIME

At 20 ° C and 60% humidity:

- \* Dust free: 15 min.
- \* Dry: 30 min.

Recoat after 4 hours.

## RECOMMENDED SYSTEM

### ■ EXTERIOR

SYSTEM	NUMBER OF COATS
ENDUIT FACADE P20 or P10 (option)	1
COLOPRIM or COLOFIX	1
COLOVINYL 900	2

### ■ INTERIOR

SYSTEM	NUMBER OF COATS
COLOPRIM or COLOFIX	1
COLENDUIT Extra B505 or SP88	2
COLOSTOP (Optional)	1
COLOVINYL 900	2

## STORAGE

The product can be stored for up to 2 years under good storage conditions away from sunlight, it is nevertheless recommended to shake the product before use.

## PACKAGING

5 Kg, 30 Kg, 45 Kg.

## HEALTH & SAFETY

Health and safety information and precautions for use are detailed on the safety data sheet N° 186.

Edition : July 2020 by Colorado 07/20 (DC28 D).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted. This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001