TECHNICAL DATA SHEET :

DAHAB MAT



DESCRIPTION

Decorative coating in waterborne, pearlescent sanded and glitter effect.

FIELD OF USE

Specially designed to beautify interiors by dressing them in a particularly warm atmosphere.

TECHNICAL CHARACTERISTICS

- Aspect : Slightly metallic and pearly with silver glitter.
- Colors : According to our color chart.
- Spreading-rate : About 7,5 m²/L (in one layer, apply by brush or brush or sponge).
- Density: 1,18 +/- 0,05 at 25° C.
- Viscosity : 33500 +/- 2500 cP in Brookfield S5 / 10 25 °C for the neutral base.

SURFACE PREPARATION

The work must be done in accordance with standard NF DTU59.1 and will be carried out with the greatest care.

CONDITIONS AND METHODS OF APPLICATION

Apply the first coat of DAHAB with a short pile roller, diluted with 5% water.

On the first well-wiped coat, apply the second and possibly the third coat of DAHAB, diluted with 5% water, with a short pile roller and smooth the surface with a stainless steel spatula with circular movements.

APPLICATION DETAILS OF USAGE

Dilution: Product ready to use. Mix the product well with a spatula before use. Can be diluted up to 5% with water.



EAU INT

DRYING TIME

Drying at 20 ° C and 60% humidity:

- * Dust free: 1 hour.
- * Dry: 5 hours.
- * Washable after 20 days (with a layer of Coloprim).

RECOMMENDED SYSTEM

INTERIOR

SYSTEM	NUMBER OF COATS
COLOPRIM or COLOFIX	1
COLENDUIT EXTRA B505 or SP88	2
COLOFONDO	1
DAHAB MAT	2
COLOPRIM (For washability)	1

STORAGE

The product can be stored for up to 2 years in good storage conditions away from sunlight, it is nevertheless recommended to shake the product before use.

PACKAGING

2 ,5 Kg.

HEALTH & SAFETY

Health and safety information and precautions for use are detailed on the safety data sheet N° 155.

Edition : July 2020 by Colorado 07/20 (DC28 D).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted.

This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001

www.colorado.ma