



DESCRIPTION

Decorative all coverin base on acrylic emulsions. INTERIOR E TERIOR .

FIELD OF USE

Particularly suitable for the construction and protection of facades, corridors, halls, waiting rooms, stairwells, etc.

TECHNICAL CHARACTERISTICS

- Aspect : Matt, granite and pasty.
- Color : hite.
- Spreading-rate : 1 to 2 Kg/m² (in two coats) depending on the porosity of the support, in accordance with ISO 23811 (2009).
- Density : 1,75 ± 0,05 at 25°C, complies with NM ISO 2811-1 (2008).
- Viscosity : 650 +/- 50 poises at 25°C at Brookfield.

SURFACE PREPARATION

The work must be done in accordance with standard NF DTU59.1 and will be carried out with the greatest care.

CONDITIONS AND METHODS OF APPLICATION

Limit of application: Do not apply on condensing or frozen support, at temperatures below 5 ° C and above 35 ° C, nor at relative humidity above 65%.

APPLICATION DETAIL

Application tool: ppl without diluting ith a 2 cm knife and simultaneousl bring out the desired decorative appearance using a suitable spr .

Application conditions compliant ith standard N 2 DT 5 . .

The preparation of the base ne or old, covered or not must be done in accordance ith standard N 2 DT 5 . .

rior recognition is necessar to determine the nature of the preparations and the possible impression.

DILUTION DICE

ead to use product.

void asting paint, estimate ho much paint ou need. Close unfinished pots so that the paint can be used again.

DRYING TIME

Drying at 20 ° C and 60% humidity:

- * Dust free: 1h30min.
- * Dry: 4 hours.
- * Recoatable: 12 hours.

RECOMMENDED SYSTEM

■ INTERIOR (Consult us):

SYSTEM	NUMBER OF COATS
SP88	1 to 2
COLOFIX	1
DECOJET	1
ACRYSAT	1 to 2

■ EXTERIOR (Consult us):

SYSTEM	NUMBER OF COATS
ENDUIT P20 or P10	1 to 2
COLOFIX	1
DECOJET	1
COLOVINYL600	1 to 2

STORAGE

The pro duct can be store or up to 2 years in oo stora e con itions a ay rom sunli ht, it is nevertheless recommen e to sha e the pro duct be ore use.

PACKAGING

25 kg.

HEALTH SAFETY

Health and safety information and precautions for use are detailed on the safety data sheet N°257.

Edition : July 2020 by Colorado 07/20 (DC28 D).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted. This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001