



## DESCRIPTION

Decorative wall covering based on acrylic emulsions.  
INTERIOR EXTERIOR .

## FIELD OF USE

Particularly suitable for the construction and protection of facades, corridors, halls, waiting rooms, stairwells, etc.

## TECHNICAL CHARACTERISTICS

- Aspect : Matt, granite and pasty.
- Color : White.
- Spreading-rate : 1 to 2 Kg/m<sup>2</sup> (in two coats) depending on the porosity of the support, in accordance with ISO 23811 (2009).
- Density : 1,75 ± 0,05 at 25°C, complies with NM ISO 2811-1 (2008).
- Viscosity : 650 +/- 50 poises at 25°C at Brookfield.

## SURFACE PREPARATION

The work must be done in accordance with standard NF DTU59.1 and will be carried out with the greatest care.

## CONDITIONS AND METHODS OF APPLICATION

Limit of application: Do not apply on condensing or frozen support, at temperatures below 5 ° C and above 35 ° C, nor at relative humidity above 65%.

## APPLICATION DETAILS OF USAGE

Application tool: Apply (without diluting) with a 20 cm knife and simultaneously bring out the desired decorative appearance using a suitable spray.

Application conditions compliant with standard NFP 74-201 (DTU 59.1).

The preparation of the base (new or old, covered or not) must be done in accordance with standard NF P 74-201 (DTU 59.1).

Prior recognition is necessary to determine the nature of the preparations and the possible impression.

## DILUTION & ADVICE

Ready to use product.

Avoid wasting paint, estimate how much paint you need.

Close unfinished pots so that the paint can be used again.

## DRYING TIME

Drying at 20 ° C and 60% humidity:

\* Dust free: 1h30min.

\* Dry: 4 hours.

\* Recoatable: 12 hours.

## RECOMMENDED SYSTEM

### ■ INTERIOR (Consult us):

SYSTEM	NUMBER OF COATS
SP88	1 to 2
COLOFIX	1
DECOJET	1
ACRYSAT	1 to 2

### ■ EXTERIOR (Consult us):

SYSTEM	NUMBER OF COATS
ENDUIT P20 or P10	1 to 2
COLOFIX	1
DECOJET	1
COLOVINYL600	1 to 2

## STORAGE

The product can be stored for up to 2 years in good storage conditions away from sunlight, it is nevertheless recommended to shake the product before use.

## PACKAGING

25 kg.

## HEALTH & SAFETY

Health and safety information and precautions for use are detailed on the safety data sheet N°257.

Edition : July 2020 by Colorado 07/20 (DC28 D).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted. This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001