



## DESCRIPTION

Printing based on alkyd resins.  
Microporous filling print.

## FIELD OF USE

FORMORAL is a print that enhances the adhesion between the support and the finishing paint. FORMORAL homogenizes funds and provides a regular finish.

The use of FORMORAL reduces the consumption of topcoat.

Use as a print on all wood and derivative supports, plaster, and old paints in good condition. It is particularly suitable for exterior work on wood.

## TECHNICAL CHARACTERISTICS

- Aspect : Satin.
- Colors: White.
- Spreading-rate : 4 to 5 m<sup>2</sup>/kg depending on the porosity of the support.
- Density : 1,57 ± 0,05 at 25°C.
- Dry extract (by weight) : 81 % +/- 2%.
- Viscosity : 100 KU +/- 5 at 25 °C (Krebs - Stormer).

## SURFACE PREPARATION

The work must be done in accordance with standard NF DTU59.1 and will be carried out with the greatest care.

## CONDITIONS AND METHODS OF APPLICATION

Recommended material: Roller, brush or gun. Do not apply on condensate or frozen substrates at temperatures below 7 ° C, nor at relative humidity above 70%.

## APPLICATION DETAILS OF USAGE

Dilution: D66 (White Spirit).

## DRYING TIME

Drying at 20 ° C and 60% humidity:

\*Dust free: 3 hours.

\*Dry: 8 hours.

\*Recoatible: 24 hours.

## STORAGE

The product can be stored for up to 2 years in good storage conditions away from sunlight and frost in its original closed packaging. It is nevertheless recommended to shake the product before use.

## PACKAGING

1Kg, 5Kg, 20 kg, 30 Kg.

## HEALTH & SAFETY

Health and safety information and precautions for use are detailed on the safety data sheet N°96.

Edition : September 2021 by Colorado 09/21 (DC28 D).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted. This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001