



DESCRIPTION

Matt paint based on modified acrylic copolymers.

FIELD OF USE

Applies to masonry, concrete, woodwork or plaster coating. ITOFACADE is an acrylic paint particularly recommended for economical facade work.

TECHNICAL CHARACTERISTICS

- Aspect : Matt.
- Colors : According to color chart.
- Spreading-rate : 5 to 6 m²/Kg depending on the porosity of the support.
- Density : 1,68 ± 0,05 kg/l at 25°C.
- Viscosity : 130 ± 5 KU with Krebs viscometer at 25 ° C.

SURFACE PREPARATION

The work must be done in accordance with standard NF DTU59.1 and will be carried out with the greatest care.

CONDITIONS AND METHODS OF APPLICATION

ITOFACADE can be applied by roller or brush without any risk of reworking or joining.
Application limit: Do not apply on condensing or frozen substrates, at temperatures below 5 ° C, or at relative humidity above 70%.

APPLICATION DETAILS OF USAGE

Dilution: up to 10% water.

DRYING TIME

- Drying at 20 ° C and 60% humidity:
- * Dust free: 15 min.
- * Dry: 30 min.
- * Interval between coats: 3 hours minimum.

RECOMMENDED SYSTEM

■ EXTERIOR

SYSTEM	NUMBER OF COATS
ENDUIT FACADE P20 or P10	1
COLOPRIM or COLOFIX	1
ITOFACADE	2

STORAGE

The product can be stored for up to 2 years under good storage conditions away from sunlight, it is nevertheless recommended to shake the product before use.

PACKAGING

5 kg, 20 kg, 30 kg.

HEALTH & SAFETY

Health and safety information and precautions for use are detailed on the safety data sheet N° 114.

Edition : July 2020 by Colorado 07/20 (DC28 D).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted. This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001