TECHNICAL DATA SHEET:

ITOTEINTE





Paste for painting in aqueous phase.

FIELD OF USE

Easy tinting of vinyl paints and decorative products.

TECHNICAL CHARACTERISTICS

- Color: Oxide red, bright red, oxide yellow, dark yellow, black, white.
- Density: 1,00 to 1,42 +/- 0.05 at 25°C (depending on the color).
- Viscosity: 85 +/- 5 KU at 25°C with the Krebs Viscometer.

APPLICATION DETAILS OF USAGE

- * Dilution: Water.
- *Incompatibility: Do not exceed 5% (weight per weight) of addition to the paintings.





STORAGE

The product can be stored for up to 2 years in good storage conditions away from sunlight and frost in its original closed packaging. It is nevertheless recommended to shake the product before use.

PACKAGING

75 ml.

HEALTH & SAFETY

Health and safety information and precautions for use are detailed on the safety data sheet N°13.

Edition: July 2020 by Colorado 07/20 (DC28 D).

N.B: The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted.

This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001