



67E5D;BF;A@

Decorative coating in aqueous phase, shimmering and glitter.

FIELD OF USE

Decorative painting with a glittering effect that gives your interior a chic atmosphere and an intimate atmosphere.

TECHNICAL CHARACTERISTICS

- Aspect : Shimmering mat.
- Colors : 30 color references (see our catalog). Spreading-rate : About 12 m²/Kg.
- Density : 1,27 +/- 0,05 at 25° C.
- Viscosity : 300 +/- 50 poises in Brookfield S6 / 10 at 25 ° C.

SURFACE PREPARATION

The work must be done in accordance with standard NF DTU59.1 and will be carried out with the greatest care.

CONDITIONS AND METHODS OF APPLICATION

Apply 1st coat of KANZ in alternating strokes using a brush (on COLOFONDO), on surfaces which do not exceed 2m² in order to avoid rapid drying during application.

The first coat can be applied with a lacquer roller.

Immediately after, lightly smooth the surface with a clean brush to achieve the desired decor.

After 4 hours, apply a 2nd coat of KANZ under the same conditions in order to obtain a better result. When the second coat of KANZ dries, lightly sand the surface with sandpaper to bring out the glitter.

APPLICATION DETAILS OF USAGE

Dilution: ready to use (can be diluted up to 5% with water).

Mix the product well with a spatula before use.

DRYING TIME

Drying at 20 ° C and 65% relative humidity:

*Dust free: 1 hour.

*Dry: 4 hours.

* Washable: 20 days.

RECOMMENDED SYSTEM (contact us)

■ INTERIOR

SYSTEM	NUMBER OF COATS
COLOPRIM or COLOFIX	1
COLENDUIT EXTRA B505 or SP88	2
COLOFONDO	1
KANZ	2

STORAGE

The product can be stored for up to 2 years in good storage conditions away from sunlight, it is nevertheless recommended to shake the product before use.

PACKAGING

2,5 kg.

HEALTH & SAFETY

Health and safety information and precautions for use are detailed on the safety data sheet N° 171.

Edition : July 2020 by Colorado 07/20 (DC28 D).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted. This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001