KASBAA





Old-fashioned decorative paste, made from water and vegetable fibers, odorless. Improves thermal and acoustic comfort of interiors. Great ease of application and allows you to hide substrate defects.

FIELD OF USE

Recommended for application on interior walls.

TECHNICAL CHARACTERISTICS

Aspect : Pasty product.

Colors: White and can be waxed with the different

shades available on our color chart.

 \blacksquare Spreading-rate: * Pate: 1,3 to 1,8 Kg/m².

*Wax : 12 to 15 m^2/L .

■ Density at 25°C: * Pate: 1,69 +/- 0,05.

*Wax: 1.00 +/- 0,05.

■ Viscosity: * Pate: 1000 +/- 200 poises.

SURFACE PREPARATION

The work must be done in accordance with standard NF DTU59.1 and will be carried out with the greatest care.

CONDITIONS AND METHODS OF APPLICATION

On a previously prepared substrate, apply KASBAA directly using a stainless steel float. Then, equalize the load to have a regular thickness. Before the paste dries, lightly smooth the applied surface using the triangular spatula. 24 hours later, apply the wax specially designed for interiors only with a soft sponge and create the desired patina effects.

APPLICATION DETAILS OF USAGE

Dilution: Product ready to use.





DRYING TIME

*Pate: 24 heures. *Wax: 30 à 45 mn.

RECOMMENDED SYSTEM

INTERIOR

SYSTEM	NUMBER OF COATS
COLOPRIM or COLOFIX	1
COLENDUIT EXTRA B505/SP88	1
COLOVINYL 600 EXTRA	1
KASBAA	1
KASBAA CIRE	1

STORAGE

The product can be stored for up to 2 years in good storage conditions away from sunlight, it is nevertheless recommended to shake the product before use.

PACKAGING

Pate : 5 kg, 25 kg Wax : 800 ml

HEALTH & SAFETY

Health and safety information and precautions for use are detailed on the safety data sheet N° 25.

Edition: October 2021 by Colorado 10/21 (DC28 D).

N.B: The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted.

This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001