



DESCRIPTION

Glossy lacquer based on Glycerophthalic resins.

FIELD OF USE

Quick-drying topcoat for general jobs.
It can be applied both indoors and outdoors on all usual properly prepared building supports (Plaster, wood, metal surfaces, etc.).

TECHNICAL CHARACTERISTICS

- Aspect : Brilliant.
- Colors: According to color chart, delivered in different colors that can be mixed together. Be held at Colopate.
- Spreading-rate: 10,7 m²/Kg/40µm depending on the color and porosity of the support.
- Density : 1,16 + / - 0,05.
- Volume-solids : 50 +/- 2%.

SURFACE PREPARATION

The work must be done in accordance with standard NF DTU59.1 and will be carried out with the greatest care.

APPLICATION PROPERTIES

Material: Brush, roller and spray.
Application limit: Do not apply on condensing or frozen substrates at temperatures below 5 ° C, nor at relative humidity above 70%.

APPLICATION DETAILS OF USAGE

Dilution: White Spirit (D66).
5 to 10% for Brush or Roller 30 to 40% for spray.

DRYING TIME

Drying at 20 ° C and 60% humidity:
* Surface-dry : 1 hour 30 minutes.
* Dry: 6 hours.
* Interval between two coats: Minimum 24 hours.

RECOMMENDED SYSTEM

■ METAL

SYSTEM (*)	NUMBER OF COATS
ANTIROUILLE (Minum Gris or Rouge)	1
METALAC	2

■ SMOOTH WOOD AND PLASTER

SYSTEM (*)	NUMBER OF COATS
FORMORAL	1
COLOSTOP	2
COLOMAT	1
METALAC	2

N.B: In this case the dilution is done only using the Whit Spirit (D66).

(*) Consult us for other systems.

STORAGE

The product can be stored for up to 1 year under good storage conditions away from sunlight and frost in its original closed packaging. It is nevertheless recommended to shake the product before use.

PACKAGING

1 kg, 5kg, 15 kg, and 20 kg..

HEALTH & SAFETY

Health and safety information and precautions for use are detailed on the safety data sheet N° 94.

Edition : July 2020 by Colorado 07/20 (DC28 D).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted. This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001