



MONOPRIM

Adhesion promoter for mortar



DESCRIPTION :

MONOPRIM is a micro-coat specially adapted to smooth surface; it's used as an adhesion bridge and base regulator before application of One-coat mortar or any other coating or mortar based made on hydraulic binders.

COMPOSITION :

Adhesion promoter based on synthetic resins, inert fillers and specific additives.

CARACTERISTICS :

- Ready to use.
- Ensures good grip and regulates absorption.
- Applicable directly on concrete wall.
- Water-proof.
- Regularization of mortar setting time.

APPLICATION DATA :

SURFACE PREPARATION:

- Remove dirt: mosses, defilement, surface mild and dust.
- Do not apply on water-repellent surface.

EXECUTION :

Before any use, the product must be mixed. Then apply with a roller or brush to smooth all the surfaces.

Wait for the MONOPRIM to dry completely (at least 12 hours) before the application of the coating. Coating application should not exceed 3 days.

Tools should be cleaned immediately after use.

DO NOT APPLY :

- In direct sunlight, threat of rain or strong wind.
- At temperatures less than 5°C or more than 30°C.
- On a wet surface.

PACKAGING :

5 kg and 20kg bucket.

STORAGE :

12 months in original intact packaging and stored in a dry place.

PRODUCT DATA :

Appearance	: Yellow colored paste
PH	: 8.5
Drying time	: 12 hours
Spreading-rate	: 300g/m ² /m ²

MINIMUM ORDER QUANTITY:

600kg.

HEALTH, SAFETY AND ENVIRONMENT :

Des informations de santé, de sécurité et des précautions d'emploi sont détaillées sur la fiche de données de sécurité N°297

Health and safety information and precautions for use are detailed on safety data sheet N°: 297.

N.B: The purpose of this technical data sheet is to provide information on the properties of our product. The information contained herein is based on our current knowledge of tests carried out with constant concern objectivity based on condition of use that comply with standards or DTU in force.

However, the information cannot be provide to a descriptive appropriate and to the condition of the funds to be coated.

This technical data sheet cancels and replaces any other sheet relating to the same product. The technical data does not entail acceptance of warranties. Help preserve the environment by not throwing residue in the sewer, in household waste. Please return your empty bags to a recycling center. For your unused product, please check with the local authorities to find out the methods of disposal and collection.

Edition : August 2025 by Colorado 08/25 (DC28G).