



## DESCRIPTION

Paint based on modified synthetic resins.

## FIELD OF USE

Sidewalk edge paint.

## TECHNICAL CHARACTERISTICS

- Appearance : Matte for white and gray
- : Satin for red, yellow, green and blue
- Spreading-rate : 5m<sup>2</sup>/ kg. Density at 25°C.
- - White : 1.69 +/- 0,05.
- - Color : 1.49 à 1.75.
- Dry extract (by weight) : 78.4 +/- 2 %.
- Viscosity : 100 +/- 5 KU.

## CONDITIONS AND METHODS OF APPLICATION

The work must be carried out in accordance with the standard NF DTU59.1 and will be carried out with the greatest care.

Application Limit : Do not apply to substrates condensing or frozen, at a temperature below 5°C.

The substrate must be sound, clean, dry and free from dust, oil, grease, ect.

The product can be applied by : roller , spray, or brush.

## APPLICATION DETAILS OF USAGE

Dilution : D44 .

## DRYING TIME

10 Hours +/- 2 H at 23°C and RH 50%.

## STORAGE

The product can be stored for up to 2 years in good storage conditions away from sunlight and frost in its original closed packaging. It is nevertheless recommended to shake the product before use.

## PACKAGING

5 kg, 25 kg .

## HEALTH & SAFETY

Health and safety information and precautions for use are detailed in the safety data sheet N° 92.

Edition : June 2024 by Colorado 06/24 (DC28 D).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted. This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 ,ISO 45001 et ISO 27001