



**DESCRIPTION**

Lacquer based on non-yellowing modified alkyd resins. Has a faint odor.

**FIELD OF USE**

PRIMOLAC is intended to enhance interior and exterior decorative elements. Easily achieve glossy finishes and exceptional durability. Has exceptional whiteness. Quick drying, without recovery or traces. Maintains by simple washing, without altering its shine.

**TECHNICAL CHARACTERISTICS**

- Aspect : Gloss.
- Colors : Delivered in white, can be tinted with our Colopates. Special tints are delivered for orders over 100 kg.
- Spreading-rate : 16 à 18 m<sup>2</sup>/Kg depending on the porosity of the support.
- Density : 1,20 + / - 0,05.
- Dry extract : 60% +/- 2%.
- Viscosity : 85 +/- 5 KU with the Krebs viscometer at 25°C.

**SURFACE PREPARATION**

The work must be done in accordance with standard NF DTU59.1 and will be carried out with the greatest care.

**APPLICATION PROPERTIES**

Material: Brush, roller and gun.  
 Application limit:  
 Do not apply on condensing or frozen substrates at temperatures below 5 °C, nor at relative humidity above 70%.

**APPLICATION DETAILS OF USAGE**

Dilution: De-flavored solvent for Primolac.

**DRYING TIME**

Drying at 20 °C and 60% humidity:  
 \*Dust free: 1 hour  
 \* Dry: 6 hours.  
 \*Interval between two coats: Minimum 24 hours.

**RECOMMENDED SYSTEM**

■ INTERIOR

SYSTEM	NUMBER OF COATS
COLOPRIM or COLOFIX	1
COLENDUIT EXTRA B505 or SP88	2
COLOSTOP	1
COLOMAT 99	1
PRIMOLAC	2

**STORAGE**

The product can be stored for up to 2 years under good storage conditions away from sunlight and frost in its original closed packaging. However, it is recommended to shake the product before use.

**PACKAGING**

1 kg, 5 kg.

**HEALTH & SAFETY**

Health and safety information and precautions for use are detailed in the safety data sheet N° 88.

Edition : July 2020 by Colorado 07/20 (DC28 D).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted. This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001