



## DESCRIPTION

Solvent-free coating based on modified epoxy resin, for interior.

## FIELD OF USE

Anti-dust paint, designed for the protection of the interiors of tanks containing non-acidic food products and drinking water.

Resipox is also a good two-component solvent-free coating for floors.

## TECHNICAL CHARACTERISTICS

- Aspect : Brilliant.
- Color : White.
- Spreading-rate : 2m<sup>2</sup>/kg/350 µm.
- Density : \* Base: 1.60+/- 0.05 .  
\*Hardener: 1.10 +/- 0.05 .  
\* Mixture: 1.40 +/- 0.05 .
- Dilution: do not dilute.

## SURFACE PREPARATION

The work must be done in accordance with standard NF DTU59.1 and will be carried out with the greatest care.

## APPLICATION PROPERTIES

The 2 components are mixed in the following proportions by weight: 80% base and 20% hardener. Pot life of the mixture at 20 ° C: 1 H.

After this period, the product builds up and becomes unusable.

The product is applied with a brush and a roller.

Application limit: Do not apply on condensing or frozen substrates at temperatures below 5 ° C, nor at relative humidity above 70%.

## DRYING TIME

Drying at 20 ° C and 60% humidity:

Through- dry : 6 hours.

Recoat after: 24 hours.

## STORAGE

The product can be stored for up to 1 year under good storage conditions away from sunlight and frost in its original closed packaging. It is nevertheless recommended to shake the product before use.

## PACKAGING

HARDENER RESIPOX: 1Kg

RESIPOX: 4Kg

## HEALTH & SAFETY

Health and safety information and precautions for use are detailed on the safety data sheet N° 87.

Edition : July 2020 by Colorado 07/20 (DC28 D).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted.

This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001