TECHNICAL DATA SHEET:

TOUAREG





Decorative paint with a pearly metallic appearance specially designed for the embellishment of interiors and provides a particularly cozy atmosphere.

FIELD OF USE

Recommended for application on interior walls.

TECHNICAL CHARACTERISTICS

- Aspect : Slightly metallic and pearly.
- Colors : According to our color chart.
- Spreading-rate: About 6 m²/L (in 2 layers), compliant with ISO 23811 (2009).
- Density: 1,07 +/- 0,05 depending on the color at 25 °C, in accordance with standard NM ISO 2811-1 (2008).
- Viscosity: 108 +/- 5 KU at 25° Cł ccomplies with ASTM D561 (1997).

SURFACE PREPARATION

The work must be done in accordance with standard NF DTU59.1 and will be carried out with the greatest care.

CONDITIONS AND METHODS OF APPLICATION

The substrate is prepared using one or two coats of Fondo (White) or Colofondo (Tinted) paint and let dry for 12 hours.

Apply the first coat of TOUAREG with a short nap roller, diluted with 20% water.

On the first, well-wiped coat, apply the second and possibly the third coat of TOUAREG, diluted with 20% water, with a short-nap roller and smooth the surface with a stainless steel spatula with circular movements.

APPLICATION DETAILS OF USAGE

Dilution: Product ready to use. Can be diluted up to 20% with tap water, depending on the application method used.





DRYING TIME

Drying at 20 ° C and 60% humidity:

- * Dust free: +/- 2 hours
- * Recoatable: 6 hours.

RECOMMENDED SYSTEM

■ INTERIOR

SYSTEM	NUMBER OF COATS
COLOPRIM or COLOFIX	1
COLENDUIT EXTRA B505 or SP88	2
COLOFONDO	1
TOUAREG	1

STORAGE

The product can be stored for up to 2 years in good storage conditions away from sunlight, it is nevertheless recommended to shake the product before use.

PACKAGING

1kg, 2.5 kg, 20 kg.

HEALTH & SAFETY

Health and safety information and precautions for use are detailed on the safety data sheet N° 65.

MINIMUM ORDER QUANTITY

Please contact our sales department.

Edition: August 2025 by Colorado 08/25 (DC28G).

N.B: The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted.

This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001, ISO 45001 and ISO 27001