# TECHNICAL DATA SHEET :

# /ERNIS DEKEAU



## DESCRIPTION

Waterborne Varnish based on a pure acrylic resin. Vernis Dekeau is a water-based varnish, designed for the protection of coatings sensitive to bad weather and which has good washability.

### FIELD OF USE

This varnish without harmful solvents, is particularly suitable for high exterior and interior decoration (wood, concrete and P.V.C) and is recommended for the protection of interior decorative coatings.

#### **TECHNICAL CHARACTERISTICS**

- Aspect : Gloss.
- Colors: Transparent.
- Spreading-rate : 9 à 10 m2/kg depending on the porosity of the support.
- Density: 1,04 +/- 0,05 at 25°C.
- Viscosity : 100 +/- 5 KU at 25°C.

#### SURFACE PREPARATION

The work must be done in accordance with standard NF DTU59.1 and will be carried out with the greatest care.

#### **CONDITIONS AND METHODS OF APPLICATION**

It is applied with a roller or possibly with a brush or spray gun on clean, dry and dust-free bases. Generally, two coats are applied diluted according to the porosity of the support.

Application limit: Do not apply on condensing or frozen substrates, at temperatures below 5  $^\circ$  C, or at relative humidity above 70%.

#### APPLICATION DETAILS OF USAGE

Dilution: 0 to 10% with water



#### DRYING TIME

At 20 ° C and 60% humidity:

- \* Dust dry: 30 min.
- \* Dry: 1 hour.
- \* Interval between coats: minimum 8 hours.

#### STORAGE

The product can be stored for up to 2 years in good storage conditions away from sunlight, it is nevertheless recommended to shake the product before use.

#### PACKAGING

800 ml.

#### HEALTH & SAFETY

Health and safety information and precautions for use are detailed on the safety data sheet N° 64.

Edition : July 2020 by Colorado 07/20 (DC28 D).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted.

This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001

